

EXPI-DOOR® Systems Inc.

Door Series Comparison Guide

	Series 300™	Series 500®	Series 600	Series 700™
Builder Price - Base Door				
Primary System	Knock Down Preassembled	Preassembled Knock Down	"Prehung"	Preassembled
EDS Overall Warranty	One Year	Two Years	Three Years	Three Years
Door Skin	20 gauge galvanized (A40) Textured skin	20 gauge galvanized (A40) Smooth skin 18 Gauge Optional	18 gauge galvanized (A60) Smooth skin	18 gauge galvanized (A60) Smooth skin
Door Reinforcements				
Top/Bot Channel	16 gauge galvanized (A40)	16 gauge galvanized (A40)	14 gauge galvanized (A60)	14 gauge galvanized (A60)
Hinge	10 Gauge	10 Gauge	7 Gauge	7 Gauge
Lock	14 Gauge	14 Gauge	14 Gauge	14 Gauge
Closer	Not Available	14 Gauge	14 Gauge	14 Gauge
Door Core	Polystyrene	Polystyrene	Polystyrene	Polystyrene
Door Edge	Beveled edge - Reversible Interlocking seam	Straight edge - Reversible Laser Welded edge Lifetime warranty	Beveled Edge Interlocking seam	Beveled Edge Interlocking seam
Frame	16 gauge galvanized (A40) Butted corner connection 5 3/4" with returns 10 gauge hinge reinforcement	16 gauge galvanized (A40) Butted corner connection 5 3/4" with returns 10 gauge hinge reinforcement (Set screws for HD hinges)	16 gauge galvanized (A60) Welded corner connection 5 3/4" with drywall returns 7 gauge hinge reinforcement (Wire plate for HD hinges)	16 gauge galvanized (A60) Welded corner connection 5 3/4" with drywall returns 7 gauge hinge reinforcement (Wire plate for HD hinges)
Paint Finish	Colored Primer (ANSI A250.1)	Finish coat paint (ANSI A250.3)	Colored Primer (ANSI A250.1)	Colored Primer (ANSI A250.1)
Subframe	KD - none PA - 16 gauge gal (A40 min) Flush mount design Jamb Trim Required	16 gauge galvanized (A40 min) Flush mount design Jamb trim required	(Supplied knock down) 16 gauge galvanized (A40 min) Offset design w/jamb anchors Self trimming - no trim required (1,000,000 cycle tested)	16 gauge galvanized (A40 min) Offset design w/jamb anchors Self trimming - no trim required (1,000,000 cycle tested)
Lock	Grade 2 Lever One year warranty	Falcon Grade 2 Lever Two year warranty	(supplied knock down) Falcon Grade 2 Lever Two year warranty Falcon line or Schlage line	Schlage Grade 2 Lever Three year warranty
Threshold	5 3/4" full aluminum	5 3/4" full aluminum	5 3/4" full aluminum	5 3/4" full aluminum
Weatherseal	Self adhesive	Self adhesive	Self adhesive	Self adhesive (options available)
Sweep	Exterior mount	TPE "U" Concealed Sweep	TPE "U" Concealed Sweep	TPE "U" Concealed Sweep (options available)
Packaging	KD doors in corrugated sleeve KD frame corrugated box PA doors in wood surround	PA Doors crated in wood	Doors individually boxed Placed on skid. Foam protectors around edges	PA doors crated in wood Foam protectors around edges
Distribution	Primarily KD stock programs	Primarily PA Just-in-Time To OEM facility or job site	Primarily PA Just-in-Time To OEM facility or job site	Primarily PA Just-in-Time To OEM facility or job site
Options	Limited	Full - Value Brands Falcon, Monarch, Dor-o-matic	Full - Highly architectural Plus Value brands	Full - Highly architectural
Other Features	130,140,150 wind rated products			Full line of accessories Great for project oriented quotes Specs and codes High level of wind rated options