

INTRODUCING...

EXPI-VIEW™ WINDOWS

BY EXPI-DOOR®



**FX-600 Fixed
Window Unit**
Sizes: 3030 & 4040



**SL-650
Horizontal-Slider**
Sizes: 4040 & 6030

- Sturdy, durable, thermally-broken aluminum frame
- NFRC Certified Product
- WDMA Hallmark Certified Product
- Fixed or Horizontal-Slider offering
- Larger thermal breaks than competitive products
- Minimal breaks or joints in the overall construction
- Cleaner lines for a more complete, finished seal and appearance
- Installs quickly using a classic “Brickmould” trim
- Smooth gliding operation of sliders
- Easy removal and attachment of glazing
- Standard AAMA 2604 powder-coat finish in WHITE or BRONZE to match EXPI-DOOR® door systems
- Glass air-space filled with Argon Gas for superior insulating factor
- All window units available as Pre-Hung in Metal Building C-Channel Sub-Frame System for quick and easy installation!

EXPI-Door Systems Inc.®

MEMBER OF THE BAY FAMILY OF COMPANIES

3146 Yeager Drive
Green Bay, WI 54311
920.393.4028
www.expidoor.com

WINDOW UNIT COMPARISON

EXPI-VIEW™ vs. The Competition

	EXPI-VIEW™	COMPETITION
FINISH	STANDARD AAMA 2604 POWDER-COAT	STANDARD AAMA 2603 BAKED POLYESTER
COLOR OPTIONS	EXPI-DOOR® WHITE & BRONZE (MATCHES OUR DOORS!)	BONE WHITE & DARK BRONZE
THERMAL-BREAK	1/8" LARGER THAN THE INDUSTRY STANDARD	INDUSTRY STANDARD WITH INDUSTRY STANDARD PERFORMANCE FACTOR
FRAME DEPTH	2 9/16"	2 7/16"
WEEPS	LARGER SLIT, REINFORCED WITH VINYL SLEEVE & WEEPSLOT COVERS TO PREVENT INFILTRATION OF INSECTS, DEBRIS & AIR FROM EXTERIOR - EASY TO CLEAN FROM INTERIOR OR EXTERIOR	SMALL SLIT, EASILY CLOGGED WITH DEBRIS, NO COVER OR PREVENTION OF INFILTRATION FROM EXTERIOR - HARD TO CLEAN
GLASS THICKNESS, FIXED WINDOWS	1" OVERALL	1" OVERALL
GLASS THICKNESS, H.S. WINDOWS	3/4" OVERALL	5/8" FOR ALL WINDOW TYPES (NO OPTIONS)

EXPI-DOOR®
S Y S T E M S I N C.

3146 Yeager Drive
Green Bay, WI 54311
Phone: 920.393.4028
Fax: 920.393.4452

