

Door Series Comparison Guide						
Door Product	Series 700 PA (BEST)	Key Features or Benefits	Series 500 PA & KD (BETTER)	Key Features or Benefits	Series 400 PA & KD (New) (GOOD)	Key Features or Benefits
Primary System	Preassembled	700 PA	Preassembled & Knockdown		Preassembled and Knockdown	
Supplier	EXPI-DOOR® Systems Inc.		EXPI-DOOR® Systems Inc.		EXPI-DOOR® Systems Inc.	
Market Fit	Heavy Duty Commercial Level 2 model 1	Best in Market	Heavy Duty Commercial Level 2 model 1	Equal to or better than market competition	Light Duty Commercial Level 1 model 1	Equal to or better than market competition
Codes/Applications Fire-Rated Wind Rated Specialty items LEED BAA	Yes, largest range- Flush Subframe up to +/-70 psf (160 mph) Flush Subframe Yes (per quoted leadtimes) Yes Yes	Best Compliance Available on the Market	Yes- Flush Subframe up to +/-70 psf (160mph) Flush Subframe Yes (per quoted lead-times) Yes Yes	Equal to or better than market competition	No No No No No	Equal to or better than market competition
Overall Warranty	Three Years	Best in Market	Three Years	Two additional years to previous	Two Years	Two additional years to previous
Cylindrical Lock	Schlage AL53PD Saturn 626 Entrance lock Grade 2 Three Year Warranty, parts or components	Recognized Allegion Industry Leading Brand	Falcon W511 Dane Cyl 6626 Grade 2 Leading Brand lockset Three Year Warranty, Parts or components	Recognized Allegion Commercial Grade Brand Improved Guarantee	Hager Model 2553 Grade 2 lockset One Year Limited Warranty, Parts or components	Recognized Allegion Commercial Grade Brand Improved Guarantee
Hardware Options	Full - Highly architectural Schlage, Von Duprin, LCN Grade 1 Schlage	Best in Market	Full line of Allegion hardware Grade 1 Falcon	Best in Market	Standard stock components of Allegion hardware Standard Grade 2 Closer, thru-bolted Grade 1 Lever / Panic Exit w/Key-in-Lever	Recognized Allegion Commercial Grade Brand
Door Skin	18 gauge galvanized (A60) Smooth skin	Our Standard is an upgrade at the competition	18 gauge Galvannealed (A60) Smooth skin	Our Standard is an upgrade at the competition	20 gauge Galvannealed (A40) Smooth skin	Our Standard is comparable to the competition
Door Reinforcements Top/Bot Channel Hinge Lock Closer	14 gauge galvanized (A60) 7 Gauge 14 Gauge 14 Gauge	Meets and/or exceeds SDI Standards	16 gauge galvanized (A60) 7 Gauge w/dust cover 14 Gauge w/dust cover 14 Gauge	Meets and/or exceeds SDI Standards	14 gauge galvanized (A640) 10 Gauge w/dust cover No 14 Gauge w/dust cover No closer reinforcement	Meets and/or exceeds SDI Standards
Door Core	Polyurthane R-11.1	Best in Market	Polyurethane R-11	Best in Market	Polystyrene R-7.03	Best in Market
Door Edge	Beveled Edge - not reversible Interlocking mechanical seam	Architectural Standards Compliant	Straight edge - Reversible Interlocking mechanical seam	Equal to or better than market competition	Straight edge - Reversible Interlocking mechanical seam	Equal to or better than market competition
Frame	5-3/4" welded A-60 Steel Frame Assembly (ANSI 250-8) MU 16-4-3070 (A60 Galv., Closer Reinforced Header Both ends) Steel Craft Frame with back bend and return.	Architectural Standards Compliant	5-3/4" 16 gauge galvanized (A60) (ASTM A653) Butted & Screwed corner connection 5 3/4" with backbend & return 7 gauge hinge reinforcement	Equal to or better than market competition	5-7/8" 18 gauge galvanized (A40) PA welded corner connection / KD is mitered tab-slot 5 7/8" with backbend 10 gauge hinge reinforcement	Equal to or better than market competition
Paint Finish	Beige Primer. One coat of baked-on rust inhibiting prime paint IAW ANSI A250.1 (IAW ANSI A250.1)	Best in Market	Colored Primer White and Antique Bronze (ANSI A250.1)	Best in Market	Colored Primer White and Antique Bronze (ANSI A250.1)	Best in Market
Subframe	16 gauge galvaneal (A60 min) Offset design is self-trimming Flush mount- Jam Trim Required (1,000,000 cycle tested)	EXPI-DOOR EXCLUSIVE Best in Market	16 gauge gal (A60 min) Offset design is self-trimming Flush mount- Jamb Trim Required	Equal to or better than market competition	16 gauge gal (A40 min) Flush Mount Only Jamb Trim Required	Equal to or better than market competition
Threshold	5 3/4" HVY/DUTY knothched full aluminum 3' ADA	Best in Market	5 3/4" HVY/DUTY knothched full aluminum 3' ADA	Best in Market	5 3/4" HVY/DUTY knothched full aluminum 3' ADA	Best in Market
Weatherseal	Self Adhesive Bulb Weather-strip (options available)	Also certified Smoke-Seal	Self Adhesive Bulb Weather-strip (options available)	Also certified Smoke-seal	Self Adhesive Bulb Weather-strip	Also certified Smoke-seal
Sweep	EPDM 3' Door Neo Bottom Dual-fingered sweep		EPDM 3' Door Neo Bottom Sweep Dual-fingered sweep		EPDM 3' Door Neo Bottom Sweep Dual-fingered sweep	
Packaging	PA doors crated in wood surround		PA & KD doors in wood surround		PA doors in wood surround KD doors packaged in corrugated and skidded	
Distribution	Doors shipped JIT to plant ship w/Building order Direct to job site when required		Doors shipped JIT to plant ship w/Building order Direct to job site when required		Doors shipped JIT to plant ship w/Building order Direct to job site when required	